







KIR-Rohre			P	K	WS	Material			
	KIR-Rohr Ø1 17.2	-20	1005	10	30.35	18.80	20.—	P	1.25
				20	41.15	25.40	27.—	K	-.95
				24	23.55	14.60	15.—		
Ø1 21.5	25	1006	10	30.80	19.10	20.—	P	1.70	
			20	41.55	25.75	27.—	K	1.25	
			24	23.95	14.95	16.—			
Ø1 28.2	32	1007	10	31.80	19.85	21.—	P	2.75	
			20	42.60	26.50	28.—	K	2.—	
			24	25.—	15.70	16.—			
Ø1 35.8	40	1008	10	42.40	26.50	28.—	P	3.95	
			20	58.—	36.10	38.—	K	2.95	
			24	29.45	18.60	19.—			



KIR-Rohre hf lichtgr									
	KIR-Rohr hf lichtgr Ø1 17.0	-20	125 140	10	32.20	20.15	21.—	P	3.10
				20	42.95	26.75	28.—	K	2.30
				24	25.35	15.95	17.—		
Ø1 21.6	25	125 141	10	33.10	20.80	22.—	P	4.—	
			20	43.85	27.45	29.—	K	2.95	
			24	26.30	16.65	17.—			
Ø1 27.7	32	125 142	10	35.35	22.50	23.—	P	6.25	
			20	46.10	29.10	30.—	K	4.60	
			24	28.55	18.30	18.—			
Ø1 35.5	40	125 143	10	46.90	29.85	30.—	P	8.45	
			20	62.50	39.40	41.—	K	6.25	
			24	33.95	21.90	22.—			

KIR-Bögen									
	KIR-Bogen steckbar	-20	1138	24	25.80	16.05	17.—	P	1.90
				K					1.40
		25	1139	24	26.40	16.55	17.—	P	2.55
				K					1.85
32	1140	24	27.25	17.15	18.—	P	3.40		
		K					2.50		
40	1147	24	30.75	19.45	20.—	P	4.55		
		K					3.35		
	KIR-Bogen -25 m Biegefeder erstellen	45-90°	1018	09	29.25	17.95	19.—		

KRH-Rohre									
	KRH-Rohr Ø1 15.8	20	1031	10	31.70	19.80	21.—	P	2.60
				20	42.45	26.40	28.—	K	1.95
				24	24.90	15.60	16.—		
Ø1 20.6	25	1032	10	32.90	20.65	21.—	P	3.80	
			20	43.65	27.25	29.—	K	2.80	
			24	26.05	16.45	17.—			
Ø1 27	32	1033	10	34.95	22.20	23.—	P	5.90	
			20	45.75	28.80	30.—	K	4.35	
			24	28.15	18.—	18.—			
Ø1 34	40	1034	10	47.30	30.10	31.—	P	8.85	
			20	62.90	39.70	41.—	K	6.55	
			24	34.35	22.20	22.—			
	KRH-Bogen m Fön erstellen	45-90°	1028	09	32.30	19.85	21.—		