







KIR-Rohre			P	K	WS	Material					
	KIR-Rohr Ø1 17.2	-20	1005	10	30.15	18.65	20.—	P	1.25		
				20	40.85	25.25	27.—	K	-.95		
				24	23.40	14.50	15.—				
	Ø1 21.5	25	1006	10	30.60	19.—	20.—	P	1.70		
				20	41.30	25.55	27.—	K	1.25		
				24	23.85	14.85	16.—				
	Ø1 28.2	32	1007	10	31.60	19.75	21.—	P	2.75		
				20	42.30	26.30	28.—	K	2.—		
				24	24.85	15.60	16.—				
	Ø1 35.8	40	1008	10	42.15	26.35	28.—	P	3.95		
				20	57.65	35.85	38.—	K	2.95		
				24	29.30	18.45	19.—				
KIR-Rohre hf lichtgr											
	KIR-Rohr hf lichtgr Ø1 17.0	-20	125 140	10	32.—	20.—	21.—	P	3.10		
				20	42.70	26.55	28.—	K	2.30		
				24	25.20	15.85	16.—				
	Ø1 21.6	25	125 141	10	32.90	20.70	21.—	P	4.—		
				20	43.60	27.25	28.—	K	2.95		
				24	26.15	16.55	17.—				
	Ø1 27.7	32	125 142	10	35.20	22.35	23.—	P	6.30		
				20	45.85	28.95	30.—	K	4.65		
				24	28.40	18.20	18.—				
	Ø1 35.5	40	125 143	10	46.—	29.20	30.—	P	7.85		
				20	61.55	38.75	40.—	K	5.80		
				24	33.20	21.35	21.—				
KIR-Bögen											
	KIR-Bogen steckbar	-20	1138	24	25.60	15.95	17.—	P	1.90		
								K	1.40		
				25	1139	24	26.25	16.40	17.—	P	2.55
										K	1.85
32	1140	24	27.10	17.05	18.—	P	3.40				
						K	2.50				
40	1147	24	30.60	19.35	20.—	P	4.55				
						K	3.35				
	KIR-Bogen -25 m Biegefeder erstellen	45-90°	1018	09	29.05	17.85	19.—				
KRH-Rohre											
	KRH-Rohr Ø1 15.8	20	1031	10	31.50	19.65	21.—	P	2.60		
				20	42.20	26.20	28.—	K	1.95		
				24	24.75	15.50	16.—				
	Ø1 20.6	25	1032	10	32.70	20.50	21.—	P	3.80		
				20	43.40	27.10	28.—	K	2.80		
				24	25.90	16.35	17.—				
	Ø1 27	32	1033	10	34.75	22.05	23.—	P	5.90		
				20	45.45	28.65	30.—	K	4.35		
				24	28.—	17.90	18.—				
	Ø1 34	40	1034	10	47.—	29.95	31.—	P	8.85		
				20	62.55	39.45	41.—	K	6.55		
				24	34.20	22.05	22.—				
	KRH-Bogen m Fön erstellen	45-90°	1028	09	32.10	19.70	21.—				